

Raynor Sentinel™ III

DC MOTOR, INTEGRATED LED & CAMERA, BELT DRIVE, EQUIPPED WITH WIFI & BLUETOOTH



84505RRGD
SMART GARAGE OPENER

POPULAR FEATURES

QUIET & SMOOTH OPERATIONS best-in-class belt drive system and DC motor provides reliable operation and lasting service

CAMERA WITH 2-WAY COMMUNICATION from a built-in 130° wide angle camera that lets you see and hear what is happening in your garage through the myQ app

INTEGRATED DUAL LED LIGHTING SYSTEM provides 1,500 lumens of long-lasting LED light that brightens high traffic areas of the garage

MYQ® CONNECTED control, secure and monitor the garage from the myQ app anytime, from anywhere

SECURE IN-GARAGE DELIVERY enables Amazon Key In-Garage Delivery - free for Amazon Prime members

SECURITY+ 2.0® sends a new code with every remote click

THE PROTECTOR SYSTEM® invisible light beam auto-reverses the door if there is an obstruction

POSILOCK® PROTECTION electronically protects against forced openings

DIAGNOSTICS myQ Diagnostics in the myQ app provides real-time insights for your garage door via the Health Report. You will be sent alerts if an issue arises and be connected to professional services if needed

IN THE BOX



MULTI-FUNCTION CONTROL PANEL

Operates the garage door opener and lights from inside the garage.

882RGDW • 6081094



3-BUTTON REMOTE CONTROL

Operate up to 3 openers or myQ light accessories from one remote

893RGX • 2220188

POWERFUL ADD-ONS



WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN

877MGX • 2220189



MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access

374UT • 2220193



MOTOR

12V DC, 53 RPM, automatic thermal protection

MECHANICS

- Steel chassis, T-rail and Trolley, full reinforced belt drive mechanism (63:1 gear reduction and adjustable door arm)
- Auto-force adjustment for changing weather and environmental conditions
- Electronic limits for easy setup
- DC WiFi logic board with built-in surge suppressor

POWER

120V AC, 60 Hz voltage, 6A current rating, UL listed, 4' power cord (3-prong)

SPEED

7.2" per second upward, 7.2" per second downward

LIGHTING

Dual light lens LED - 1,500 lumens

DIMENSIONS

Opener Head: 10.5" L x 12.72" W x 8.185" H

Note: when both decorative doors are open, the width of the opener is 30".

Rail Options:	7'	8'	10'
Installed Length	127"	139"	163"
Max Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

MOUNTING

Side-to-Side



WARRANTIES

Lifetime: Belt and Motor

1 Year: Parts, Camera, Accessories and LED



SECURITY+ 2.0®

Radio Controls:

- Operating range ~200'
- Operating temperature: -40°F to 150°F
- 3-Button remote control with Security+ 2.0 code format
- Garage door opener with Security+ 2.0 code format
- Anti-burglary coding

Encrypted Controls:

- Multi-Function Control Panel
- Program Remote Controls
- Maintenance Alert System
- Easy WiFi Setup

MYQ RADIO

- 902-928 MHz 50-channel FHSS (frequently hopping spread spectrum)
- Provides 2-way communication from garage door opener and myQ accessories
- Enables monitoring and control of garage door openers via smartphone or tablet

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER)

May require an external adapter depending on the model and year of vehicle. Visit [HomeLink.com](https://www.homelink.com) for additional information.



SHIPPING

Carton 1 Shipping Details

Dimensions: 14" x 12" x 11"

Weight: 19.4 lbs

Contents:

- Garage Door Opener Head
- Multi-Function Control Panel
- 3-Button Remote Controls
- The Protector System® Safety Reversing Sensors

Carton 2 Shipping Details

Dimensions: 10'4" x 5" x 5" (for 7' Rail)

Weight: 17 lbs

Contents:

- Assembled solid steel, belt drive T-rail