Raynor Sentinel[™] 360

DC LED BATTERY BACKUP BELT DRIVE WIFI & BLUETOOTH WITH INTEGRATED CAMERA



87504RRGD-267 SMART GARAGE OPENER

POPULAR FEATURES

QUIET & SMOOTH OPERATIONS best-in-class belt drive system and DC motor provides reliable operation and lasting service

CAMERA WITH 2-WAY COMMUNICATION from a built-in 140° wide angle camera that lets you see and hear what is happening in your garage through the myQ app

LED CORNER TO CORNER LIGHTING increases the functionality of the garage with 2,000 lumens of LED light provided on a 360° built in ring

MYQ[®] CONNECTED control, secure and monitor the garage from the myQ app anytime, from anywhere

SECURE IN-GARAGE DELIVERY enables Amazon Key In-Garage Delivery - free for Amazon Prime members

SECURITY+ 2.0[®] sends a new code with every remote click

THE PROTECTOR SYSTEM® invisible light beam autoreverses the door if there is an obstruction

POSILOCK® PROTECTION electronically protects against forced openings

DIAGNOSTICS myQ Diagnostics in the myQ app provides real-time insights for your garage door via the Health Report. You will be sent alerts if an issue arises and connected to professional services if needed

BUILT-IN WIFI AND BLUETOOTH for the easiest way to connect the garage

SMART CONTROL PANEL® Intuitive menu-driven panel lets you easily program remote controls, adjust settings, and even get system diagnostics.

880RGDW • 6081093



IN THE BOX

3-BUTTON REMOTE CONTROL Operate up to 3 openers or myQ light accessories from one remote

893RGX • 2220188



INTEGRATED BATTERY BACKUP Powers up the opener when the power is out



WIRELESS KEYLESS ENTRY Provides convenient, secure access from outside the garage with a 4-digit PIN

877MGX • 2220189

485LM • 6080759

POWERFUL ADD-ONS



SMART TOUCHSCREEN DEADBOLT Smartphone control securely lock, unlock and view door activity in the myQ app

SGC1WLM • 6081054



MINI UNIVERSAL REMOTE CONTROL Compact and portable to provide quick, easy garage access

374UT • 2220193





MOTOR

12V DC, 53 RPM, automatic thermal protection, permanent lubrication

MECHANICS

- Steel chassis, T-rail and Trolley, full reinforced belt drive mechanism (63:1 gear reduction and adjustable door arm)
- Auto-force adjustment for changing weather and environmental conditions
- Electronic limits for easy setup
- DC WiFi logic board with built-in Bluetooth surge suppressor

POWER

120V AC, 60 Hz voltage, 2.7 current rating, UL listed, 4' power cord (3-prong)

SPEED

9" per second upward, 6.5" per second downward

LIGHTING

2,000 lumens integrated LED (360°)

DIMENSIONS

Opener Head: 10.5" L x 18.7" W x 8.185" H Note: when both decorative doors are open, the width of the opener is 30".

Rail Options:	7'	8'	10'
Installed Length	124"	139"	163"
Max Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

WARRANTIES Lifetime: Belt and Motor

5 Years: LED and Parts 1 Year: Battery, Camera and Accessories

SECURITY+ 2.0®

Radio Controls:

- Operating range ~200'
- Operating temperature: -40°F to 150°F
- (2) 3-button remote controls with Security+ 2.0 code format
- Garage door opener with Security+ 2.0 code format
- · Anti-burglary coding

Encrypted Controls:

- Smart Control Panel[®]
- Timer-to-Close
- Program Remote Controls
- · Keypads and myQ accessories
- Maintenance Alert System
- Easy WiFi Setup

MYQ RADIO

- 902-928 MHz 50-channel FHSS (frequently hopping spread spectrum)
- Provides 2-way communication from garage door opener and myQ accessories
- Enables monitoring and control of garage door openers via smartphone
 or tablet

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER)

May require an external adapter depending on the model and year of vehicle. Visit HomeLink.com for additional information.

Jo-B			
SHIPPING			
Carton 1 Shipping Details	Carton 2 Shipping Details		
Dimensions: 20.1" x 12.1" x 9.7" Weight: 25 lbs Contents: • Garage Door Opener Head • Battery • Smart Control Panel • (2) 3-Button Remote Controls • Wireless Keyless Entry System • The Protector System [®] Safety Reversing Sensors	Dimensions: 10'4" x 5" x 5" (for 7' Rail) Weight: 17 lbs Contents: • Assembled Solid-Steel Belt T-Rail		

t: To reduce the risk of injury to persons, only enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.