

Sergeant™ II with WiFi®

DC BATTERY BACKUP WIFI OPENER WITH INTEGRATED BLUETOOTH TECHNOLOGY



81602RGD

TRUSTED RELIABILITY
WITH BATTERY BACKUP

POPULAR FEATURES

DC MOTOR is purposefully designed for quiet performance

CHAIN DRIVE SYSTEM for steady performance and industrial strength

SOFT START/STOP for smooth operation

BUILT-IN WIFI for the easiest way to connect the garage

INTEGRATED BLUETOOTH TECHNOLOGY Reduces setup time and makes it even easier to connect to the myQ app, other myQ devices and smart home technology solutions

MYQ MOBILE APP lets users receive alerts and control the opener from anywhere

SECURITY+ 2.0® safeguards garage access by sending a new code with every click

POSILOCK® electronically protects against forced openings

ALERT-2-CLOSE signals when a door is being closed by myQ

THE PROTECTOR SYSTEM® invisible light beam auto-reverses the door if there is an obstruction

IN THE BOX



MULTI-FUNCTION CONTROL PANEL

Operates the garage door opener and lights from inside the garage

882RGDW • 6081094



3-BUTTON REMOTE CONTROL

Operate up to 3 openers or MyQ light accessories from one remote

893RGX • 2220188



INTEGRATED BATTERY BACKUP

Powers up the opener when the power is out

485LM • 6080759

POWERFUL ADD-ONS



MYQ SMART CAMERA

Enable secure video capabilities in your garage

SGC1WLM • 6081054



MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access

374UT • 2220193

Sergeant™ II with WiFi®

DC BATTERY BACKUP WIFI OPENER WITH INTEGRATED BLUETOOTH TECHNOLOGY



MOTOR

12V DC, 53 RPM, automatic thermal protection, permanent lubrication

MECHANICS

- Steel chassis, T-rail and Trolley, full chain drive mechanism (63:1 gear reduction and adjustable door arm)
- Auto-force adjustment for changing weather and environmental conditions
- Electronic limits for easy setup
- DC WiFi logic board with built-in surge suppressor

POWER

120V AC, 60 Hz voltage, 2.7A current rating, UL listed, 4' power cord (3-prong)

SPEED

8.5" per second upward, 6.5" per second downward

LIGHTING

100 watt light bulb, enhanced CFL (Compact Florescent) compatible, max. 26 watts, solid-state light delay, adjustable time, disabled in battery backup mode

DIMENSIONS

Opener Head: 15.2" L x 10.5" W x 7.67" H

Rail Options:	7'	8'	10'
Installed Length	128"	140"	164"
Max Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"



SECURITY+ 2.0®

Radio Controls:

- Operating range ~200'
- Operating temperature: -30°F to 150°F
- 3-button remote control with Security+ 2.0 code format
- Keyless entry with Security+ 2.0 code format
- Anti-burglary coding

Encrypted Controls:

- Multi-Function Control Panel®
- Program Remote Controls
- Maintenance Alert System
- Easy WiFi Setup

MYQ RADIO

- 902-928 MHz 50-channel FHSS (frequently hopping spread spectrum)
- Provides 2-way communication from garage door opener and myQ accessories
- Enables monitoring and control of garage door openers via smartphone or tablet

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER)

May require an external adapter depending on the model and year of vehicle. Visit HomeLink.com for additional information.



SHIPPING

Carton 1 Shipping Details

Dimensions: 19.81" x 11.94" x 11.19"

Weight: 22 lbs

Contents:

- Garage Door Opener Head
- Battery
- Multi-Function Control Panel
- 3-Button Remote Control

Carton 2 Shipping Details

Dimensions: 10'4" x 5" x 5"
(for 7' Rail)

Weight: 20 lbs

Contents:

- Assembled Solid-Steel Chain T-Rail



WARRANTIES

4 Years: Motor

1 Year: Battery and Accessories

*: To reduce the risk of injury to persons, only enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.